

PRODUCT INFORMATION

Issue Date: 28.04.2026

CK 640 GORE BOA SF

SAFETY BOOT DIN EN ISO 20345:2024 S3S HI CI SR HRO FO
SIZES: 36 - 52 (225 - 337) | FITTING OPTIONS: NB, XB (S, XXB)



S3S PROTECTION CLASS S3S
according DIN EN ISO 20345

STEITZ FLEX-ZONE®
Outsole with flexion zone

TEXTILE PUNCTURE RESISTANCE
highly flexible, metal free
puncture resistance

DGUV 191 INSOLE TREATMENT
tested according to
DGUV Rule 112-191

BOA® FIT SYSTEM
for a fast, effortless, precision fit.

ORIGINAL STEITZ MULTI-WIDTH SYSTEM
4 different widths per shoe size

COMPOSITE TOE CAP
Metal free toe cap, made of
composite materials

ESD
Protection against electrostatic
discharge

GORE-TEX
Membrane system, waterproof and
highly breathable

Engineered with



GORE-TEX
Performance Comfort
Footwear



FEATURES

- + GORE-TEX membrane
- + Full-grained, hydrophobic smooth leather combined with breathable textile inserts
- + BOA® Fit System
- + Dust guard tongue

- + Reinforced, abrasion-resistant toe guard
 - + High visibility safety reflectors
- Full-length, removable comfort insole ERGO-SOFT ESD with cushioning system and excellent moisture transportation

OUTSOLE

Perbunan CK ESD, slate-grey

- + Outsole with a profile of 3 mm
- + Best possible anti-slip properties on slippery, wet or oily surfaces
- + Hard-wearing and excellent cut resistance
- + Flexion zone with pivot point
- + Broad contact surface
- + Durable against acid and oil-based substances
- + Heat-resistant up to approx. 220 °C, heat resistant in the short term up to approx. 300 °C



CUSHIONING

Universal shock absorption

Universal shock absorption through soft-foamed PU midsole. Additionally, the removable and comfortably soft comfort insole provides best possible moisture transportation.

