

CK 7520 PERBUNAN SF

SAFETY SHOE EN ISO 20345:2011 S3 SRC CI HRO

SIZES: 36 - 52 (225 - 337) | FITTING OPTIONS: NB, XB (S, XXB)



PROTECTION CLASS S3
according EN ISO 20345



STEITZ FLEX-ZONE®
Outsole with flexion zone



TEXTILE PUNCTURE RESISTANCE
highly flexible, metal free
puncture resistance



ESD
Protection against electrostatic
discharge



ORIGINAL STEITZ MULTI-WIDTH SYSTEM
4 different widths per shoe size



COMPOSITE TOE CAP
Metal free toe cap, made of composite
materials



METAL FREE



INSOLE TREATMENT
tested according to
DGV Rule 112-191

FEATURES

- + Full-grained, easy-care smooth leather
- + Reinforced, abrasion-resistant toe guard
- + Dust guard tongue
- + High visibility safety reflectors
- + Metal-free design
- + Functional lining made of breathable textile and microfibre
- + Full-length, removable comfort insole ERGO-SOFT ESD with cushioning system and excellent moisture transportation

OUTSOLE

Perbunan CK ESD, grey

- + Outsole with a profile of 3 mm
- + Best possible anti-slip properties on slippery, wet or oily surfaces
- + Hard-wearing and excellent cut resistance
- + Flexion zone with pivot point
- + Broad contact surface
- + Durable against acid and oil-based substances
- + Heat-resistant up to approx. 220 °C, heat resistant in the short term up to approx. 300 °C



CUSHIONING

Universal shock absorption

Universal shock absorption through soft-foamed PU midsole. Additionally, the removable and comfortably soft comfort insole provides best possible moisture transportation.

