

NF 696 QRS S3

FOUNDY BOOT EN ISO 20349-1:2017 S3 FE AI CI HRO SRC EN  
ISO 20345:2011 S3 CI HRO SRC

SIZES: 38 - 48/49 (240 - 315) | FITTING OPTIONS: NB, XB (XXB)



- S3** PROTECTION CLASS S3  
according EN ISO 20345

**STEEL MIDSOLE**  
puncture resistant steel midsole

**DGUV 191** INSOLE TREATMENT  
tested according to  
DGUV Rule 112-191
- STEEL TOE CAP**  
Toe cap made of steel

**LEATHER-INSOLE**

FEATURES

- + Aluminised smooth leather
- + Quick-Removal-System
- + Functional grip
- + Fire resistant Kevlar® yarn
- + Ankle protection
- + Soft vamp-lining made of real leather
- + Replaceable comfort insole with heat-resistant aluminium coating

OUTSOLE

**Perbunan Zermatt**, anthracite

- + Outsole with a profile of 7,0 mm
- + Best possible anti-slip properties on slippery, wet or oily surfaces
- + Hard-wearing and excellent cut resistance
- + Broad contact surface
- + Durable against acid and oil-based substances
- + Heat-resistant up to approx. 220 °C

CUSHIONING

**Universal shock absorption**

Universal shock absorption through soft-foamed PU midsole. Additionally, the removable and comfortably soft comfort insole provides best possible moisture transportation.