

VD 3500 GORE SST SF

SAFETY SHOE EN ISO 20345:2011 S3 SRC CI FO HRO
SIZES: 36 - 48/49 (225 - 315) | FITTING OPTIONS: NB, XB (S, XXB)



- S3** PROTECTION CLASS S3
according EN ISO 20345

AL ALUMINIUM TOE CAP
Toe cap made of aluminium

ESD
Protection against electrostatic discharge

GORE-TEX
Membrane system, waterproof and highly breathable
- 4** ORIGINAL STEITZ MULTI-WIDTH SYSTEM
4 different widths per shoe size

SF TEXTILE PUNCTURE RESISTANCE
highly flexible, metal free
puncture resistance

DGUV 191 INSOLE TREATMENT
tested according to
DGUV Rule 112-191



FEATURES

- + GORE-TEX membrane
- + Ultralight microfibre
- + Comfortable fit due to seamless shoe design
- + Dust guard tongue

- + Full-length, removable comfort insole ERGO-SOFT ESD with cushioning system and excellent moisture transportation

OUTSOLE

Perbunan Athletic ESD, slategrey

- + Outsole with a profile of 3,8 mm
- + Light and flexible with tailored arch support
- + Flexion zone with pivot point
- + Cushioning structure in the heel area
- + Best possible scuff resistance and anti-slip properties
- + Heat-resistant up to approx. 220 °C

CUSHIONING

Multiflex® Technology

Lever arms of the shoe force the foot to make unnatural movements and can lead to foot and Achilles tendon complaints, knee pain and back problems. Furthermore, lever arm forces can increase the risk of injuries such as sprained ankles. Lever arm reduced shoes are characterized by lower heel heights, increased insertion depth, softer material and lesser thickness of the sole, which is rounded in the peripheral areas. A result of the Multiflex® technology is the multiflexible outsole.