

VX 7520 BAU PERBUNAN

SAFETY SHOE EN ISO 20345:2011 S3 SRC CI HRO HI

SIZES: 38 - 48/49 (240 - 315) | FITTING OPTIONS: NB, XB (S, XXB)



- S3** PROTECTION CLASS S3
according EN ISO 20345

SECURA VARIO® SYSTEM
weight dependent heel shock
absorption

ALUMINIUM TOE CAP
Toe cap made of aluminium

ESD
Protection against electrostatic
discharge

**DGUV
191** INSOLE TREATMENT
tested according to
DGUV Rule 112-191
- ORIGINAL STEITZ MULTI-WIDTH SYSTEM**
4 different widths per shoe size

STEITZ FLEX-ZONE®
Outsole with flexion zone

STEEL MIDSOLE
puncture resistant steel midsole

LEATHER-INSOLE

FEATURES

- + Full-grained, easy-care smooth leather
- + Reinforced, abrasion-resistant toe guard
- + High visibility safety reflectors
- + Dust guard tongue
- + Functional lining made of breathable textile and microfibre
- + Full-length, removable comfort insole ERGO-SOFT ESD with cushioning system and excellent moisture transportation

OUTSOLE

- Perbunan VX ESD, grey**
- + Outsole with a profile of 3,8 mm
 - + Flexion zone with pivot point
 - + Hard-wearing and excellent cut resistance
 - + Broad contact surface
 - + Best possible scuff resistance and anti-slip properties
 - + Heat-resistant up to approx. 220 °C



CUSHIONING

SECURA VARIO® System

The replaceable, weight and pressure dependent heel shock absorption system ensures cushioning adapted to the individual needs of the wearer. The pressure load in the shoe is reduced to a natural extent and provides targeted relief to the back. At the same time, it helps to significantly reduce fatigue and increases the ability to compensate pressure loads by the leg and trunk musculature.

- above 105 kg
- up to 105 kg
- up to 91 kg
- up to 79 kg
- up to 57 kg



The AGR quality cachet (Aktion Gesunder Rücken = Campaign for Healthier Backs): Certified and recommended by Association Forum Healthy Back – Better Living and Federal Association of German Back Schools.
More information:
AGR e.V., Stader Str. 6, D - 27432 Bremervörde,
Phone +49 4761/92 63 580, www.agr-ev.de

