### PRODUCT INFORMATION



## VX 7750 PERBUNAN S3

SAFETY BOOT EN ISO 20345:2022 S3 HI CI SC SR HRO FO SIZES: 36 - 50 (225 - 322) I FITTING OPTIONS: NB, XB (S, XXB)





PROTECTION CLASS S3 according EN ISO 20345



SECURA VARIO® SYSTEM
weight dependent heel shock
absorption



**STEEL MIDSOLE** puncture resistant steel midsole



LEATHER-INSOLE



ORIGINAL STEITZ MULTI-WIDTH SYSTEM



ALUMINIUM TOE CAP
Toe cap made of aluminium



**ESD**Protection against electrostatic discharge



INSOLE TREATMENT tested according to DGUV Rule 112-191

# FATURES

- + Full-grained, easy-care smooth leather
- + Dust guard tongue
- + High visibility safety reflectors
- + Reinforced, abrasion-resistant toe guard
- + Cushioned collar for additional comfort

- + Functional lining made of breathable textile and microfibre
- Full-length, removable comfort insole ERGO-SOFT ESD
   with cushioning system and excellent moisture transportation

## UTSOLE

#### Perbunan Active ESD, anthracite

- + Outsole with a profile of 4,1 mm
- + Light and flexible with tailored arch support
- + Durable against acid and oil-based substances
- + Broad contact surface
- + High durability
- + Heat-resistant up to approx. 220 °C



# CUSHIONING

#### VARIO Multiflex® Technology

Lever arms of the shoe force the foot to make unnatural movements and can lead to foot and Achilles tendon complaints, knee pain and back problems. Furthermore, lever arm forces can increase the risk of injuries such as sprained ankles. Lever arm reduced shoes are characterized by lower heel heights, increased insertion depth, softer material and lesser thickness of the sole, which is rounded in the peripheral areas. A result of the VARIO Multiflex® technology is the multiflexible outsole.





The AGR quality cachet (Aktion Gesunder Rücken = Campaign for Healthier Backs): Certified and recommended by Association Forum Healthy Back - Better Living and Federal Association of German Back Schools.

More information:

AGR e.V., Stader Str. 6, D - 27432 Bremervörde,

Phone +49 4761/92 63 580, www.agr-ev.de

