PRODUCT INFORMATION



CK 8600 GTX PERBUNAN SF

SAFETY BOOT EN ISO 20345:2011 S3 SRC CI HRO SIZES: 36 - 52 (225 - 337) | FITTING OPTIONS: NB, XB (S, XXB)





PROTECTION CLASS S3 according EN ISO 20345



STEITZ FLEX-ZONE®



TEXTILE PUNCTURE RESISTANCE highly flexible, metal free puncture resistance



Protection against electrostatic



ORIGINAL STEITZ MULTI-WIDTH SYSTEM 4 different widths per shoe size



COMPOSITE TOE CAPMetal free toe cap, made of composite materials



METAL FREE



INSOLE TREATMENT tested according to DGUV Rule 112-191



- + GORE-TEX membrane
- + Hydrophobic oily nubuck leather combined with breathable textile inserts
- + Dust guard tongue
- + Reinforced, abrasion-resistant toe guard
- + High visibility safety reflectors

- + Cushioned collar for additional comfort
- + Metal-free design
- + Full-length, removable comfort insole ERGO-SOFT ESD with cushioning system and excellent moisture transportation

Perbunan CK ESD, grey

- + Outsole with a profile of 3 mm
- + Best possible anti-slip properties on slippery, wet or oily surfaces
- + Hard-wearing and excellent cut resistance
- + Flexion zone with pivot point
- + Broad contact surface
- + Durable against acid and oil-based substances
- + Heat-resistant up to approx. 220 °C, heat resistant in the short term up to approx. 300 °C



CUSHIONING

Universal shock absorption

Universal shock absorption through soft-foamed PU midsole. Additionally, the removable and comfortably soft comfort insole provides best possible moisture transportation.

