

CP 4100 BOA SF

SAFETY SHOE EN ISO 20345:2011 S1P SRC
SIZES: 36 - 50 (225 - 322) | FITTING OPTIONS: NB, XB (S, XXB)



- S1P** **PROTECTION CLASS S1P**
according EN ISO 20345,
additional puncture resistance

COMPOSITE TOE CAP
Metal free toe cap, made of compo-
site materials

ESD
Protection against electrostatic
discharge

BOA® FIT SYSTEM
for a fast, effortless, precision fit.
- ORIGINAL STEITZ MULTI-WIDTH SYSTEM**
4 different widths per shoe size

TEXTILE PUNCTURE RESISTANCE
highly flexible, metal free
puncture resistance

INSOLE TREATMENT
tested according to
DGVV Rule 112-191



FEATURES

- + Ultra-light microfibre and large-scale inserts of netting with high ventilation quality
- + BOA® Fit System
- + Reinforced, abrasion-resistant toe guard

- + Functional lining made of breathable textile and microfibre
- + Full-length, removable comfort insole ERGO-SOFT ESD with cushioning system and excellent moisture transportation

OUTSOLE

TPU Competition ESD, white

- + Outsole with a profile of 3 mm
- + With increased protection against twisted ankles, reduced lever arms
- + Light and flexible
- + Cushioning structure in the heel area
- + Best possible scuff resistance and anti-slip properties
- + Heat-resistant up to approx. 120 °C

CUSHIONING

REBOUND Technology

In the heel area, proven standard PU material stabilizes and absorbs the energy at the heel touchdown. In the midfoot and forefoot area, the midsole material with rebound effect returns a very high part of the energy spent by the wearer. In addition, the outsole made of soft TPU optimizes the power transmission in the step sequence.