

CP 4340 SF

SAFETY SHOE EN ISO 20345:2011 S3 SRC

SIZES: 36 - 50 (225 - 322) | FITTING OPTIONS: NB, XB (S, XXB)



S3 PROTECTION CLASS S3
according EN ISO 20345

4 ORIGINAL STEITZ MULTI-WIDTH SYSTEM
4 different widths per shoe size

C COMPOSITE TOE CAP
Metal free toe cap, made of composite materials

METAL FREE

SF TEXTILE PUNCTURE RESISTANCE
highly flexible, metal free
puncture resistance

ESD
Protection against electrostatic discharge

DGUV 191 INSOLE TREATMENT
tested according to
DGUV Rule 112-191

FEATURES

- + Ultra-light smooth microfibre with striking high frequency embossing
- + Comfortable fit due to seamless shoe design
- + Reinforced, abrasion-resistant toe guard
- + Metal-free design with protection against perforation
- + Functional lining made of breathable textile and microfibre
- + Full-length, removable comfort insole ERGO-SOFT ESD with cushioning system and excellent moisture transportation

OUTSOLE

TPU Competition ESD, silvergrey

- + Outsole with a profile of 3 mm
- + With increased protection against twisted ankles, reduced lever arms
- + Light and flexible
- + Cushioning structure in the heel area
- + Best possible scuff resistance and anti-slip properties
- + Heat-resistant up to approx. 120 °C



CUSHIONING

REBOUND Technology

In the heel area, proven standard PU material stabilizes and absorbs the energy at the heel touchdown. In the midfoot and forefoot area, the midsole material with rebound effect returns a very high part of the energy spent by the wearer. In addition, the outsole made of soft TPU optimizes the power transmission in the step sequence.

