

CP 4500 ESD

SAFETY SHOE EN ISO 20345:2011 S2 SRC

SIZES: 36 - 50 (225 - 322) | FITTING OPTIONS: NB, XB (S, XXB)



- S2** **PROTECTION CLASS S2**
according EN ISO 20345

COMPOSITE TOE CAP
Metal free toe cap, made of composite materials

ESD
Protection against electrostatic discharge

DGUV 191 **INSOLE TREATMENT**
tested according to DGUV Rule 112-191
- VARIO REBOUND**
Energy return plus weight dependent heel shock absorption

METAL FREE

LEATHER-INSOLE

FEATURES

- + Full-grained, easy-care smooth leather
- + Athletic design with heel strap
- + Comfortable fit due to seamless shoe design
- + Metal-free design
- + Functional lining made of breathable textile and microfibre

- + Full-length, removable comfort insole ERGO-SOFT ESD with cushioning system and excellent moisture transportation

OUTSOLE

TPU Competition ESD, black

- + Outsole with a profile of 3 mm
- + With increased protection against twisted ankles, reduced lever arms
- + Light and flexible
- + Cushioning structure in the heel area
- + Best possible scuff resistance and anti-slip properties
- + Heat-resistant up to approx. 120 °C

CUSHIONING

VARIO REBOUND Technology

We combine our proven individual and weight-adapted SECURA VARIO® heel shock absorption with intelligent rebound properties. In the heel area, proven standard PU material stabilizes and absorbs the energy at the heel touchdown. In the midfoot and forefoot area, the midsole material with rebound effect returns a very high part of the energy spent by the wearer. In addition, the outsole made of soft TPU optimizes the power transmission in the step sequence. Combined with the SECURA VARIO® system, this achieves optimal damping and a safe stance.

- above 105 kg
- up to 105 kg
- up to 91 kg
- up to 79 kg
- up to 57 kg

The AGR quality cachet (Aktion Gesunder Rücken = Campaign for Healthier Backs): Certified and recommended by Association Forum Healthy Back – Better Living and Federal Association of German Back Schools. More information: AGR e.V., Stader Str. 6, D - 27432 Bremervörde, Phone +49 4761/92 63 580, www.agr-ev.de