

CP 4800 SF

SAFETY BOOT EN ISO 20345:2011 S3 SRC

SIZES: 36 - 50 (225 - 322) | FITTING OPTIONS: NB, XB (S, XXB)



- S3** **PROTECTION CLASS S3**
according EN ISO 20345
- ORIGINAL STEITZ MULTI-WIDTH SYSTEM**
4 different widths per shoe size
- COMPOSITE TOE CAP**
Metal free toe cap, made of composite materials
- TEXTILE PUNCTURE RESISTANCE**
highly flexible, metal free puncture resistance
- METAL FREE**
- ESD**
Protection against electrostatic discharge
- INSOLE TREATMENT**
tested according to DGVU Rule 112-191

FEATURES

- + Modern textile with striking high-frequency embossing
- + Comfortable fit due to seamless shoe design
- + Reinforced, abrasion-resistant toe guard
- + Metal-free design
- + Cushioned collar for additional comfort

- + Functional lining made of breathable textile and microfibre
- + Full-length, removable comfort insole ERGO-SOFT ESD with cushioning system and excellent moisture transportation

OUTSOLE

TPU Competition ESD, black

- + Outsole with a profile of 3 mm
- + With increased protection against twisted ankles, reduced lever arms
- + Light and flexible
- + Cushioning structure in the heel area
- + Best possible scuff resistance and anti-slip properties
- + Heat-resistant up to approx. 120 °C

CUSHIONING

REBOUND Technology

In the heel area, proven standard PU material stabilizes and absorbs the energy at the heel touchdown. In the midfoot and forefoot area, the midsole material with rebound effect returns a very high part of the energy spent by the wearer. In addition, the outsole made of soft TPU optimizes the power transmission in the step sequence.