

ESD AL 711 PLUS

SAFETY SANDAL EN ISO 20345:2011 S1 SRC

SIZES: 36 - 48/49 (225 - 315) | FITTING OPTIONS: NB, XB (S, XXB)



- S1** PROTECTION CLASS S1
according EN ISO 20345

SECURA VARIO® SYSTEM
weight dependent heel shock
absorption

ALUMINIUM TOE CAP
Toe cap made of aluminium

LEATHER-INSOLE
- ORIGINAL STEITZ MULTI-WIDTH SYSTEM**
4 different widths per shoe size

STEITZ FLEX-ZONE®
Outsole with flexion zone

ESD
Protection against electrostatic
discharge

INSOLE TREATMENT
tested according to
DGV Rule 112-191

FEATURES

- + Light-weight microfibre combined with open-cell functional textile elements
- + Elastic bands and an individually adjustable velcro fastening strap for an ideal support
- + High visibility safety reflectors
- + Functional lining made of breathable textile and microfibre
- + Full-length, removable comfort insole ERGO-SOFT ESD with cushioning system and excellent moisture transportation

OUTSOLE

- TPU Dynamics ESD, silvergrey**
- + Outsole with a profile of 2,6 mm
 - + Light and flexible with tailored arch support
 - + Flexion zone with pivot point
 - + Cushioning structure in the heel area
 - + Best possible scuff resistance and anti-slip properties
 - + Heat-resistant up to approx. 120 °C



CUSHIONING

SECURA VARIO® System

The replaceable, weight and pressure dependent heel shock absorption system ensures cushioning adapted to the individual needs of the wearer. The pressure load in the shoe is reduced to a natural extent and provides targeted relief to the back. At the same time, it helps to significantly reduce fatigue and increases the ability to compensate pressure loads by the leg and trunk musculature.

- above 105 kg
- up to 105 kg
- up to 91 kg
- up to 79 kg
- up to 57 kg



The AGR quality cachet (Aktion Gesunder Rücken = Campaign for Healthier Backs): Certified and recommended by Association Forum Healthy Back – Better Living and Federal Association of German Back Schools.
More information:
AGR e.V., Stader Str. 6, D - 27432 Bremervörde,
Phone +49 4761/92 63 580, www.agr-ev.de

