

ESD DX 711 SF

SAFETY SANDAL EN ISO 20345:2011 S1P SRC
SIZES: 36 - 48/49 (225 - 315) | FITTING OPTIONS: NB, XB (S, XXB)



- S1P** PROTECTION CLASS S1P according EN ISO 20345, additional puncture resistance

STEITZ FLEX-ZONE® Outsole with flexion zone

SF TEXTILE PUNCTURE RESISTANCE highly flexible, metal free puncture resistance
- 4** ORIGINAL STEITZ MULTI-WIDTH SYSTEM 4 different widths per shoe size

AL ALUMINIUM TOE CAP Toe cap made of aluminium

ESD Protection against electrostatic discharge

FEATURES

- + Light-weight microfibre combined with open-cell functional textile elements
- + Elastic bands and an individually adjustable velcro fastening strap for an ideal support
- + High visibility safety reflectors

- + Functional lining made of breathable textile and microfibre
- + Full-length, removable comfort insole ERGO-SOFT ESD with cushioning system and excellent moisture transportation

OUTSOLE

TPU Dynamics ESD, silvergrey

- + Outsole with a profile of 2,6 mm
- + Light and flexible with tailored arch support
- + Flexion zone with pivot point
- + Cushioning structure in the heel area
- + Best possible scuff resistance and anti-slip properties
- + Heat-resistant up to approx. 120 °C

CUSHIONING

Universal shock absorption

Universal shock absorption through soft-foamed PU midsole. Additionally, the removable and comfortably soft comfort insole provides best possible moisture transportation.