

HAMAR GTX S3

SAFETY SHOE EN ISO 20345:2011 S3 SRC CI HRO
SIZES: 36 - 48/49 (225 - 315) | FITTING OPTIONS: NB, XB (S, XXB)



- S3** PROTECTION CLASS S3
according EN ISO 20345

SECURA VARIO® SYSTEM
weight dependent heel shock
absorption

STEEL MIDSOLE
puncture resistant steel midsole

LEATHER-INSOLE

GORE-TEX
Membrane system, waterproof and
highly breathable
- ORIGINAL STEITZ MULTI-WIDTH SYSTEM**
4 different widths per shoe size

ALUMINIUM TOE CAP
Toe cap made of aluminium

ESD
Protection against electrostatic
discharge

INSOLE TREATMENT
tested according to
DGV 191

Engineered with
GORE-TEX
GORE-TEX
Performance Comfort
Footwear

FEATURES

- + GORE-TEX membrane
- + Full-grained, hydrophobic smooth leather
- + Reinforced, abrasion-resistant toe guard
- + High visibility safety reflectors
- + Dust guard tongue
- + Full-length, removable comfort insole ERGO-SOFT ESD
with cushioning system and excellent moisture transportation

OUTSOLE

- Perbunan Dynamics ESD, slate-grey**
- + Outsole with a profile of 2,6 mm
 - + Light and flexible with tailored arch support
 - + Flexion zone with pivot point
 - + Cushioning structure in the heel area
 - + Best possible scuff resistance and anti-slip properties
 - + Heat-resistant up to approx. 220 °C



CUSHIONING

SECURA VARIO® System

The replaceable, weight and pressure dependent heel shock absorption system ensures cushioning adapted to the individual needs of the wearer. The pressure load in the shoe is reduced to a natural extent and provides targeted relief to the back. At the same time, it helps to significantly reduce fatigue and increases the ability to compensate pressure loads by the leg and trunk musculature.

- above 105 kg
- up to 105 kg
- up to 91 kg
- up to 79 kg
- up to 57 kg



The AGR quality cachet (Aktion Gesunder Rücken = Campaign for Healthier Backs): Certified and recommended by Association Forum Healthy Back – Better Living and Federal Association of German Back Schools.
More information:
AGR e.V., Stader Str. 6, D - 27432 Bremervörde,
Phone +49 4761/92 63 580, www.agr-ev.de

