

MED 1500 PERBUNAN

MED-SAFETY BOOT EN ISO 20345:2011 S3 SRC  
SIZES: 38 - 48 | FITTING OPTIONS: 12 UND 15



- S3** PROTECTION CLASS S3  
according EN ISO 20345

**SF** TEXTILE PUNCTURE RESISTANCE  
highly flexible, metal free  
puncture resistance
- AL** ALUMINIUM TOE CAP  
Toe cap made of aluminium

**DGUV 191** INSOLE TREATMENT  
tested according to  
DGUV Rule 112-191

FEATURES

- + Soft nubuck leather
- + Collar made of textile
- + Seamless and cushioned inner lining made of microfibres
- + Dust guard tongue
- + Full-length, removable comfort insole ORTHO-MED ESD with cushioning system and excellent moisture transportation

OUTSOLE

**Perbunan New York, anthracite**

- + Outsole with a profile of 6,5 mm
- + Best possible anti-slip properties on slippery, wet or oily surfaces
- + Hard-wearing and excellent cut resistance
- + Broad contact surface
- + Durable against acid and oil-based substances
- + Heat-resistant up to approx. 220 °C

CUSHIONING

**Universal shock absorption**

Universal shock absorption through soft-foamed PU midsole. Additionally, the removable and comfortably soft comfort insole provides best possible moisture transportation.