

MED 1600 ESD

MED-SAFETY BOOT EN ISO 20345:2011 S3 SRC

SIZES: 38 - 47 | FITTING OPTIONS: 12 UND 15



S3 **PROTECTION CLASS S3**
according EN ISO 20345

SF **TEXTILE PUNCTURE RESISTANCE**
highly flexible, metal free
puncture resistance

**DGUV
191** **INSOLE TREATMENT**
tested according to
DGUV Rule 112-191

AL **ALUMINIUM TOE CAP**
Toe cap made of aluminium

ESD
Protection against electrostatic
discharge

FEATURES

- + Full-grained, easy-care smooth leather
- + Collar made of textile
- + Seamless and cushioned inner lining made of microfibre
- + Dust guard tongue
- + Full-length, removable comfort insole ORTHO-MED ESD
- + with cushioning system and excellent moisture transportation

OUTSOLE

- TPU Jura Ortho ESD, anthracite**
- + Outsole with a profile of 4,5 mm
 - + Broad contact surface
 - + Best possible scuff resistance and anti-slip properties
 - + Heat-resistant up to approx. 120 °C



CUSHIONING

Universal shock absorption

Universal shock absorption through soft-foamed PU midsole. Additionally, the removable and comfortably soft comfort insole provides best possible moisture transportation.

