

RABEA

WOMEN COMFORT SHOE EN ISO 20347:2012 O2 FO SRC
SIZES: 35 - 42 (217 - 270) | FITTING OPTIONS: NB, XB (\$, XXB)



- 02** **PROTECTION CLASS O2**
according EN ISO 20347

SECURA VARIO® SYSTEM
weight dependent heel shock absorption

ESD
Protection against electrostatic discharge

DGUV 191 **INSOLE TREATMENT**
tested according to DGUV Rule 112-191
- 4** **ORIGINAL STEITZ MULTI-WIDTH SYSTEM**
4 different widths per shoe size

METAL FREE

LEATHER-INSOLE

FEATURES

- + Ultra-light smooth microfibre with striking high frequency embossing
- + Comfortable fit due to seamless shoe design
- + Reinforced, abrasion-resistant TPU-toe guard
- + TPU heel trim for stabilization
- + Dust flap
- + Metal-free design

- + Without toe cap
- + Functional lining made of breathable textile and microfibre
- + Full-length, removable comfort insole ERGO-SOFT ESD with cushioning system and excellent moisture transportation

OUTSOLE

TPU Woman Sport ESD, silvergrey

- + Outsole with a profile of 3 mm
- + Light and flexible
- + With tailored arch support
- + Best possible scuff resistance and anti-slip properties
- + Heat-resistant up to approx. 120 °C

CUSHIONING

VARIO Multiflex® Technology

Lever arms of the shoe force the foot to make unnatural movements and can lead to foot and Achilles tendon complaints, knee pain and back problems. Furthermore, lever arm forces can increase the risk of injuries such as sprained ankles. Lever arm reduced shoes are characterized by lower heel heights, increased insertion depth, softer material and lesser thickness of the sole, which is rounded in the peripheral areas. A result of the VARIO Multiflex® technology is the multiflexible outsole.

- above 105 kg
- up to 105 kg
- up to 91 kg
- up to 79 kg
- up to 57 kg

The AGR quality cachet (Aktion Gesunder Rücken = Campaign for Healthier Backs): Certified and recommended by Association Forum Healthy Back – Better Living and Federal Association of German Back Schools. More information: AGR e.V., Stader Str. 6, D - 27432 Bremervörde, Phone +49 4761/92 63 580, www.agr-ev.de