### PRODUCT INFORMATION



## **VD 1510 SMC SF**

## SAFETY SHOE EN ISO 20345:2011 S3 SRC CI HRO M SIZES: 36 - 50 (225 - 322) | FITTING OPTIONS: NB, XB (S, XXB)



PROTECTION CLASS \$3 according EN ISO 20345









ORIGINAL STEITZ MULTI-WIDTH SYSTEM
4 different widths per shoe size



**TEXTILE PUNCTURE RESISTANCE**highly flexible, metal free
puncture resistance



Protection against electrostatic discharge



# **EATURES**

- + Ultralight microfibre
- + Comfortable fit due to seamless shoe design
- + Dust guard tongue
- + Reinforced, abrasion-resistant toe guard
- + Metatarsal protection SECURA META COVER

- + Functional lining made of breathable textile and microfibre
- Full-length, removable comfort insole ERGO-SOFT ESD
   with cushioning system and excellent moisture transportation

# UTSOLE

#### Perbunan Athletic ESD, slategrey

- + Outsole with a profile of 3,8 mm
- + Light and flexible with tailored arch support
- + Flexion zone with pivot point
- + Cushioning structure in the heel area
- + Best possible scuff resistance and anti-slip properties
- + Heat-resistant up to approx. 220 °C



# CUSHIONING

#### Multiflex® Technology

Lever arms of the shoe force the foot to make unnatural movements and can lead to foot and Achilles tendon complaints, knee pain and back problems. Furthermore, lever arm forces can increase the risk of injuries such as sprained ankles. Lever arm reduced shoes are characterized by lower heel heights, increased insertion depth, softer material and lesser thickness of the sole, which is rounded in the peripheral areas. A result of the Multiflex\* technology is the multiflexible outsole.

