

VD 3500 BOA SST SF

SAFETY SHOE EN ISO 20345:2011 S3 SRC CI HRO

SIZES: 36 - 50 (225 - 322) | FITTING OPTIONS: NB, XB (S, XXB)



- S3** PROTECTION CLASS S3 according EN ISO 20345
- AL** ALUMINIUM TOE CAP Toe cap made of aluminium
- ESD** Protection against electrostatic discharge
- BOA** BOA® FIT SYSTEM for a fast, effortless, precision fit.

- 4** ORIGINAL STEITZ MULTI-WIDTH SYSTEM 4 different widths per shoe size
- SF** TEXTILE PUNCTURE RESISTANCE highly flexible, metal free puncture resistance
- DGUV 191** INSOLE TREATMENT tested according to DGUV Rule 112-191



FEATURES

- + Ultralight, smooth microfibre
- + Comfortable fit due to seamless shoe design
- + BOA® Fit System
- + Reinforced, abrasion-resistant toe guard
- + Dust guard tongue

- + Functional lining made of breathable textile and microfibre
- + Full-length, removable comfort insole ERGO-SOFT ESD with cushioning system and excellent moisture transportation

OUTSOLE

Perbunan Athletic ESD, slategrey

- + Outsole with a profile of 3,8 mm
- + Light and flexible with tailored arch support
- + Flexion zone with pivot point
- + Cushioning structure in the heel area
- + Best possible scuff resistance and anti-slip properties
- + Heat-resistant up to approx. 220 °C

CUSHIONING

Multiflex® Technology

Lever arms of the shoe force the foot to make unnatural movements and can lead to foot and Achilles tendon complaints, knee pain and back problems. Furthermore, lever arm forces can increase the risk of injuries such as sprained ankles. Lever arm reduced shoes are characterized by lower heel heights, increased insertion depth, softer material and lesser thickness of the sole, which is rounded in the peripheral areas. A result of the Multiflex® technology is the multiflexible outsole.