### PRODUCT INFORMATION



### **VD 3500 SST**

### SAFETY SHOE EN ISO 20345:2011 S2 SRC CI HRO SIZES: 36 - 50 (225 - 322) | FITTING OPTIONS: NB, XB (S, XXB)





PROTECTION CLASS S2 according EN ISO 20345



SECURA VARIO® SYSTEM
weight dependent heel shock
absorption



Protection against electrostatic discharge





ORIGINAL STEITZ MULTI-WIDTH SYSTEM



ALUMINIUM TOE CAP
Toe cap made of aluminium



LEATHER-INSOLE

# FATURES

- + Ultralight, smooth microfibre
- + Comfortable fit due to seamless shoe design
- + Dust guard tongue
- + Reinforced, abrasion-resistant toe guard

- + Functional lining made of breathable textile and microfibre
- Full-length, removable comfort insole ERGO-SOFT ESD
   with cushioning system and excellent moisture transportation

## UTSOLE

#### Perbunan Athletic ESD, slategrey

- + Outsole with a profile of 3,8 mm
- + Light and flexible with tailored arch support
- + Flexion zone with pivot point
- + Cushioning structure in the heel area
- + Best possible scuff resistance and anti-slip properties
- + Heat-resistant up to approx. 220 °C



# CUSHIONING

#### VARIO Multiflex® Technology

Lever arms of the shoe force the foot to make unnatural movements and can lead to foot and Achilles tendon complaints, knee pain and back problems. Furthermore, lever arm forces can increase the risk of injuries such as sprained ankles. Lever arm reduced shoes are characterized by lower heel heights, increased insertion depth, softer material and lesser thickness of the sole, which is rounded in the peripheral areas. A result of the VARIO Multiflex® technology is the multiflexible outsole.





The AGR quality cachet (Aktion Gesunder Rücken = Campaign for Healthier Backs): Certified and recommended by Association Forum Healthy Back - Bether Living and Federal Association of German Back Schools. More information:

AGR e.V., Stader Str. 6, D - 27432 Bremervörde, Phone +49 4761/92 63 580, www.agr-ev.de

