

VD 6691

SAFETY SLIPPER EN ISO 20345:2011 S2 SRC
SIZES: 36 - 48/49 (225 - 315) | FITTING OPTIONS: NB, XB (S, XXB)



- S2** PROTECTION CLASS S2
according EN ISO 20345
- SECURA VARIO® SYSTEM**
weight dependent heel shock
absorption
- AL** ALUMINIUM TOE CAP
Toe cap made of aluminium
- DGUV
191** INSOLE TREATMENT
tested according to
DGUV Rule 112-191
- 4** ORIGINAL STEITZ MULTI-WIDTH SYSTEM
4 different widths per shoe size
- STEITZ FLEX-ZONE®**
Outsole with flexion zone
- LEATHER-INSOLE**

FEATURES

- + White microfibre
- + Functional lining made of breathable textile and microfibre
- + Full-length, removable comfort insole ERGO-SOFT with cushioning system and excellent moisture transportation

OUTSOLE

TPU Dynamics, silvergrey

- + Outsole with a profile of 2,6 mm
- + Light and flexible with tailored arch support
- + Flexion zone with pivot point
- + Cushioning structure in the heel area
- + Best possible scuff resistance and anti-slip properties
- + Heat-resistant up to approx. 120 °C

CUSHIONING

SECURA VARIO® System

The replaceable, weight and pressure dependent heel shock absorption system ensures cushioning adapted to the individual needs of the wearer. The pressure load in the shoe is reduced to a natural extent and provides targeted relief to the back. At the same time, it helps to significantly reduce fatigue and increases the ability to compensate pressure loads by the leg and trunk musculature.

above 105 kg

up to 105 kg

up to 91 kg

up to 79 kg

up to 57 kg

The AGR quality cachet (Aktion Gesunder Rücken = Campaign for Healthier Backs): Certified and recommended by Association Forum Healthy Back – Better Living and Federal Association of German Back Schools. More information: AGR e.V., Stader Str. 6, D - 27432 Bremervörde, Phone +49 4761/92 63 580, www.agr-ev.de