











# PRODUCT INFORMATION

## VX 7620 BOA SMC S3

**SAFETY BOOT EN ISO 20345:2011 S3 SRC CI HRO M**  
**SIZES: 36 - 50 (225 - 322) | FITTING OPTIONS: NB, XB (\$, XXB)**



- |   |   |
|---|---|
|  <b>PROTECTION CLASS S3</b><br>according EN ISO 20345                  |  <b>ORIGINAL STEITZ MULTI-WIDTH SYSTEM</b><br>4 different widths per shoe size |
|  <b>SECURA VARIO® SYSTEM</b><br>weight dependent heel shock absorption |  <b>ALUMINIUM TOE CAP</b><br>Toe cap made of aluminium                         |
|  <b>STEEL MIDSOLE</b><br>puncture resistant steel midsole              |  <b>SECURA META COVER (SMC)</b><br>Flexible metatarsal protection              |
|  <b>ESD</b><br>Protection against electrostatic discharge              |  <b>LEATHER-INSOLE</b>   |
|  <b>INSOLE TREATMENT</b><br>tested according to DGVU Rule 112-191      |  <b>BOA® FIT SYSTEM</b><br>for a fast, effortless, precision fit.              |




**FEATURES**

- + Full-grained, easy-care smooth leather
- + BOA® Fit System
- + Reinforced, abrasion-resistant toe guard
- + Dust guard tongue
- + Metatarsal protection SECURA META COVER
- + Cushioned collar for additional comfort
- + Functional lining made of breathable textile and microfibre
- + Full-length, removable comfort insole ERGO-SOFT ESD with cushioning system and excellent moisture transportation

**OUTSOLE**

**Perbunan Active ESD, anthracite**

- + Outsole with a profile of 4,1 mm
- + Light and flexible with tailored arch support
- + Durable against acid and oil-based substances
- + Broad contact surface
- + High durability
- + Heat-resistant up to approx. 220 °C



**CUSHIONING**

**VARIO Multiflex® Technology**

Lever arms of the shoe force the foot to make unnatural movements and can lead to foot and Achilles tendon complaints, knee pain and back problems. Furthermore, lever arm forces can increase the risk of injuries such as sprained ankles. Lever arm reduced shoes are characterized by lower heel heights, increased insertion depth, softer material and lesser thickness of the sole, which is rounded in the peripheral areas. A result of the VARIO Multiflex® technology is the multiflexible outsole.



|   |              |
|---|--------------|
|  | above 105 kg |
|  | up to 105 kg |
|  | up to 91 kg  |
|  | up to 79 kg  |
|  | up to 57 kg  |



The AGR quality cachet (Aktion Gesunder Rücken = Campaign for Healthier Backs): Certified and recommended by Association Forum Healthy Back – Better Living and Federal Association of German Back Schools. More information: AGR e.V., Stader Str. 6, D - 27432 Bremervörde, Phone +49 4761/92 63 580, [www.agr-ev.de](http://www.agr-ev.de)

