

PRODUCT INFORMATION

Date of issue: 31 July 2025

CP 4400 BOA SF

SAFETY SHOE EN ISO 20345:2011 S1P SRC

SIZES: 36 - 50 (225 - 322) | FITTING OPTIONS: NB, XB, S, XXB



- **PROTECTION CLASS S1P**
according EN ISO 20345
- **COMPOSITE TOE CAP**
Metal free toe cap, made of composite materials
- **ESD**
Protection against electrostatic discharge
- **INSOLE TREATMENT**
tested according to DGV Rule 112-191
- **VARIO REBOUND**
Energy return plus weight dependent heel shock absorption
- **TEXTILE PUNCTURE RESISTANCE**
highly flexible, metal free puncture resistance
- **ORIGINAL STEITZ MULTI-WIDTH SYSTEM**
4 different widths per shoe size



FEATURES


- + Modern mesh textile
- + Athletic design with heel strap
- + Comfortable fit due to seamless shoe design
- + Reinforced, abrasion-resistant toe guard

- + Functional lining made of breathable textile and microfibre
- + Full-length, removable comfort insole ERGO-SOFT ESD with cushioning system and excellent moisture transportation

OUTSOLE

TPU Competition ESD, black

- + Outsole with a profile of 3 mm
- + With increased protection against twisted ankles, reduced lever arms
- + Light and flexible
- + Cushioning structure in the heel area
- + Best possible scuff resistance and anti-slip properties
- + Heat-resistant up to approx. 120 °C



CUSHIONING

REBOUND Technology

In the heel area, our proven standard PU material is used, which stabilises and absorbs energy during heel strike. In the midfoot and forefoot area, the midsole material with rebound effect returns a very high part of the energy expended by the wearer. In addition, the outsole made of soft TPU optimises the power transmission in the step sequence.

