

PRODUCT INFORMATION

Issue Date: 03.11.2025



VD 741 ESD

SAFETY SHOE DIN EN ISO 20345:2024 S1 SR FO
SIZES: 36 - 50 (225 - 322) | FITTING OPTIONS: NB, XB (S, XXB)



- S1**
PROTECTION CLASS S1
according EN ISO 20345
- SECURA VARIO® SYSTEM**
weight dependent heel shock absorption
- ESD**
Protection against electrostatic discharge
- DGV 191**
INSOLE TREATMENT
tested according to DGV Rule 112-191
- ORIGINAL STEITZ MULTI-WIDTH SYSTEM**
4 different widths per shoe size
- ALUMINIUM TOE CAP**
Toe cap made of aluminium
- LEATHER-INSOLE**

FEATURES

- + Ultralight microfibre
- + Perforation in the vamp and quarter for optimal ventilation
- + High visibility safety reflectors
- + Functional lining made of breathable textile and microfibre
- + Full-Length, removable comfort insole ERGO-SOFT ESD with cushioning system and excellent moisture transportation

OUTSOLE

TPU Athletic ESD, silvergrey

- + Outsole with a profile of 3,5 mm
- + With increased protection against twisted ankles, reduced lever arms
- + Supports the natural movement
- + Light and flexible
- + Very good scuff resistance and anti-slip properties
- + Heat-resistant up to approx. 120 °C

CUSHIONING

VARIO Multiflex® Technology

Lever arms of the shoe force the foot to make unnatural movements and can lead to foot and Achilles tendon complaints, knee pain and back problems. Furthermore, lever arm forces can increase the risk of injuries such as sprained ankles. Lever arm reduced shoes are characterized by lower heel heights, increased insertion depth, softer material and lesser thickness of the sole, which is rounded in the peripheral areas. A result of the VARIO Multiflex® technology is the multiflexible outsole.

above 105 kg

up to 105 kg

up to 91 kg

up to 79 kg

up to 57 kg

The AGR quality cachet (Aktion Gesunder Rücken = Campaign for Healthier Backs): Certified and recommended by Association Forum Healthy Back – Better Living and Federal Association of German Back Schools. More information: AGR e.V., Stader Str. 6, D - 27432 Bremervörde, Phone +49 4761/92 63 580, www.agr-ev.de

Geprüft & empfohlen
AGR